

SAFETY DATA SHEET**AKDRY MIX 3**

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier****Product name** AKDRY MIX 3**1.2. Relevant identified uses of the substance or mixture and uses advised against****Identified uses** Industrial use.**Uses advised against** No specific uses advised against are identified.**1.3. Details of the supplier of the safety data sheet****Supplier** AKPA KİMYA AMBALAJ SANAYİ VE TİCARET ANONİM ŞİRKETİ

Beşyol Mah. Birlik Cad. No:12 34295 Küçükçekmece

İstanbul / Turkey

Web: www.akpakimya.com

TEL: +90 212 580 55 59

FAX: +90 212 580 55 21

E-mail: info@akpakimya.com

Contact person Export Department - export@akpakimya.com**1.4. Emergency telephone number****Emergency telephone** AKPA Kimya : +90 212 580 55 59**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification (EC 1272/2008)****Physical hazards** Flam Liq. 3 H226**Health hazards** Skin Irrit. 2 H315, Eye dam.1 H318, Asp. Tox. H304, STOT SE 3 H336, Repr. 2 H361d; STOT RE 1 H372**Environmental hazards** Aquatic Acute 1 H400, Aquatic Chronic 2 H411**2.2. Label elements****Pictogram****Signal Word** Danger

H226 Flammable liquid and vapour.

Hazard statements H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

SAFETY DATA SHEET

AKDRY MIX 3

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

H361d Suspected of damaging the unborn child.
H372 May cause damage to organs.
H400 Very toxic to aquatic life
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242 Use only non-sparking tools.
P270 Do not eat, drink or smoke when using this product.
P261 Avoid breathing vapour/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301+310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician
P302+352 IF ON SKIN: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P363 Wash contaminated clothing before reuse.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P391 Collect spillage.
P501 Dispose of contents/ container in accordance with national regulations.

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Contains calcium bis (2-ethylhexanoate), Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), 2-ethylhexanoic acid, zirconium salt

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

2-ethylhexanoic acid, zirconium salt		%10-15	
CAS Numarası	22464-99-9	EC Numarası	245-018-1
Classification			
Repr. 2	H361d		

octanoic acid, manganese salt		%10-15	
CAS Number	6535-19-9	EC Number	229-437-7
Classification			
Skin Irrit. 2;	H315		



ORGANIC PEROXIDES, INITIATORS
PAINT DRIERS



SAFETY DATA SHEET AKDRY MIX 3

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

calcium bis (2-ethylhexanoate)		%10-15	
CAS Number	136-51-6	EC Number	205-249-0
Classification			
Eye Dam.1	H318		
Repr. 2	H361d		

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		%45-50	
REACH Reg. No: 01-2119458049-33-0007			
CAS Number	64742-82-1	EC Number	919-446-0
Classification			
Flam liq. 3	H226		
Asp. Tox. 1	H304		
STOT SE 3	H336		
STOT RE 1	H372		
Aquatic Chronic 2	H411		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Inhalation

Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place. Get medical attention if any discomfort continues.

Ingestion

Rinse mouth thoroughly with water. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. Get medical attention if any discomfort continues.

Skin contact

It is important to remove the substance from the skin immediately. Take off immediately all contaminated clothing. Rinse immediately with plenty of water. Get medical attention if symptoms are severe or persist after washing.

SAFETY DATA SHEET

AKDRY MIX 3

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes. Get medical attention if symptoms are severe or persist after washing.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation A single exposure may cause the following adverse effects: Difficulty in breathing. Unconsciousness. Vapors may irritate the respiratory system. Frequent inhalation of vapors over a long period of time increases the risk of developing lung diseases.

Ingestion May cause sensitization or allergic reactions in sensitive individuals. May cause discomfort if swallowed. May cause stomach pain or vomiting.

Skin contact May cause skin sensitisation or allergic reactions in sensitive individuals. Causes severe burns. Symptoms following overexposure may include the following: Pain or irritation. Redness. Blistering may occur.

Eye contact Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically. May cause sensitization or allergic reactions in sensitive individuals.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing Media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot

SAFETY DATA SHEET

AKDRY MIX 3

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard.

Hazardous decomposition products

Thermal decomposition or combustion products may include the following substances: Very toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions

Avoid or minimise the creation of any environmental contamination.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Use only non-sparking tools. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Do not empty into

SAFETY DATA SHEET

AKDRY MIX 3

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

6.4. Reference to other sections

Reference to the other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Keep container tightly sealed when not in use. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store away from other materials. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters
Occupational exposure limits

SAFETY DATA SHEET

AKDRY MIX 3

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Ingredients	CAS No.	Value	Control Parameters	Note
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1	TWA	50 ppm 290 mg/m ³	WEL
		STEL	100 ppm 580 mg/m ³	

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Workers	Dermal	Long-term - systemic effects	44 mg/kg bw/day
	Workers	Inhalation	-	330 mg/m ³
	Consumers	Dermal	Long-term - systemic effects	26 mg/kg bw/day
	Consumers	Inhalation	Long-term - systemic effects	71 mg/m ³
	Consumers	Oral	Long-term - systemic effects	26 mg/kg bw/day
	Workers	Inhalation	Long-term - systemic effects	570 mg/m ³

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimize worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimize exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

SAFETY DATA SHEET

AKDRY MIX 3

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Wear suitable mask. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14 387 and EN143. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.
Environmental exposure controls	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Violet Blue
Odour	Slight odour.
Melting point	Not available



ORGANIC PEROXIDES, INITIATORS
PAINT DRIERS



SAFETY DATA SHEET

AKDRY MIX 3

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Flash point	No data available.
Bulk density	Not available.
Solubility(ies)	Insoluble in water.
Viscosity	1,5 - 2,5 mPa.s (@20°C)
Density	0,84 ± 0,01 gr/cm ³ (@20°C)

9.2. Other information

Solid Content (%)	22 ± 2 %
--------------------------	----------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Not available.
-------------------	----------------

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	No potentially hazardous reactions.
---	-------------------------------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Static electricity and formation of sparks must be prevented. Avoid exposure to high temperatures or direct sunlight.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Oxidising agents.
---------------------------	-------------------

10.6. Hazardous decomposition products

Hazardous decomposition products

Combustion products may include the following substances: Harmful gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects



ORGANIC PEROXIDES, INITIATORS
PAINT DRIERS



SAFETY DATA SHEET

AKDRY MIX 3

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Toxicological information

The product is not tested.

Serious eye damage/irritation:

Causes serious eye damage.

Respiratory or skin sensitisation:

Skin sensitisation

May cause sensitisation by skin contact.

Germ cell mutagenicity:

Genotoxicity - In Vitro

Not available.

Genotoxicity - In Vivo

Not available.

Carcinogenicity:

Not available.

Reproductive Toxicity:

Reproductive Toxicity - Fertility

Possible risk of impaired fertility.

Reproductive Toxicity - Development

Possible risk of harm to the unborn child.

Specific target organ toxicity - single exposure:

STOT - Single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure:

STOT - Repeated exposure

May cause damage to organs.

Toxicological information on ingredients.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Acute oral toxicity	LD50: >15,000 mg/kg	Species: Rat
Acute dermal toxicity	LD50: >3,400 mg/kg	Species: Rabbit
Acute inhalation toxicity	LC50 (Rat): >13.1 mg/l	Exposure time: 4h

General information

Vapors and liquid may irritate the eyes and the respiratory system. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

AKPAORGANIC PEROXIDES, INITIATORS
PAINT DRIERS

SAFETY DATA SHEET

AKDRY MIX 3

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Aspiration Hazard	May be fatal if swallowed and enters airways.
Inhalation	A single exposure may cause the following adverse effects: Difficulty in breathing. Dizziness or unconsciousness.
Ingestion	May cause sensitisation or allergic reactions in sensitive individuals. May cause chemicalburns in mouth, oesophagus and stomach. Symptoms following overexposure may include the following: Severe stomach pain. Nausea, vomiting.
Skin contact	May cause skin sensitisation or allergic reactions in sensitive individuals. Symptoms following overexposure may include the following: irritation. Redness. Blistering may occur.
Eye contact	Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.
Route of entry	Ingestion Inhalation Skin and/or eye contact
Target organs	Respiratory system, lungs.
Medical considerations	Skin disorders and allergies.

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity No data available.

Ecological information on ingredients.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Toxicity to fish EC₅₀, 96h (Oncorhynchus mykiss): 10-30 mg/l

Toxicity to algae EC₅₀, 72h: 4.6 - 10 mg/l

Toxicity to daphnia and other EC₅₀, 48h: 10 - 20 mg/l

aquatic invertebrates

(Chronic toxicity)

12.2. Persistence and degradability

Persistence and degradability The product is readily biodegradable.

12.3. Bio accumulative potential

Bio accumulative potential No data available on bioaccumulation.

AKPAORGANIC PEROXIDES, INITIATORS
PAINT DRIERS

SAFETY DATA SHEET

AKDRY MIX 3

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

12.4. Mobility in soil

Mobility The product is insoluble in water and may spread in the aquatic environment.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Hazardous to the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods

Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Containers should be thoroughly emptied before disposal because of the risk of a fire. Do not cut or weld used containers unless they have been thoroughly cleaned internally.

SECTION 14: Transport information

General

For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

14.1. UN number

UN No. (ADR/RID)	1993
UN No. (IMDG)	1993
UN No. (ICAO)	1993
UN No. (ADN)	1993

14.2. UN proper shipping name

SAFETY DATA SHEET

AKDRY MIX 3

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Proper shipping name (ADR/RID)	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))
Proper shipping name (IMDG)	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))
Proper shipping name (ICAO)	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))
Proper shipping name (ADN)	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3
Transport labels	



14.4. Packing group	III
ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS	F-E, S-E
ADR transport category	3

SAFETY DATA SHEET AKDRY MIX 3

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Emergency Action Code 3Y
Hazard Identification Number (ADR/RID) 30
Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL Not Applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).
The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].
EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Commission Regulation (EU) No 2015/830 of 28 May 2015.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Key literature references and sources for data This SDS is prepared based on the information received from the product owner.

Classification procedures according to Regulation (EC) 1272/2008 Skin Irrit. 2 H315, Eye dam.1 H318, Asp. Tox. H304, STOT SE 3 H336, Repr. 2 H361; STOT RE 1 H372: Calculation method. Aquatic Acute 1 H400, Aquatic Chronic 2 H411: Calculation method. Flam Liq. 3 H226: Expert Judgement

Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this material.

AKPAORGANIC PEROXIDES, INITIATORS
PAINT DRIERS

SAFETY DATA SHEET

AKDRY MIX 3

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Revision comments	Revised Section 3	
Issued by	Simge ARIK - lab@akpakimya.com	+90 282 361 80 99
Revision date	31.05.2019	
Revision	1.0	
Supersedes date	28.02.2017	
Hazard statements in full	<p>H226 Flammable liquid and vapour.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H315 Causes skin irritation.</p> <p>H318 Causes serious eye damage.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H361d Suspected of damaging the unborn child.</p> <p>H372 May cause damage to organs.</p> <p>H411 Toxic to aquatic life with long-lasting effects.</p>	

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.