

SAFETY DATA SHEET**AKPEROX LPT-N**

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product name AKPEROX LPT-N
Chemical name Methyl Ethyl Ketone Peroxide

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial use.
Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier AKPA KİMYA AMBALAJ SANAYİ VE TİCARET ANONİM ŞİRKETİ
 Yenibosna Merkez Mah. Ladin Sok.
 No:36/70 Kat:12 34197 Townofis Bahçelievler, İstanbul, TÜRKİYE
 Web: www.akpakimya.com
 TEL: +90 212 580 55 59
 FAX: +90 212 580 55 21
 E-mail: info@akpakimya.com

Contact person Export Department - export@akpakimya.com

1.4. Emergency telephone number

Emergency telephone AKPA Kimya : +90 212 580 55 59

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification (EC 1272/2008)**

Physical hazards Org. Perox. D - H242
Health hazards Acute Tox. 4 - H302; Skin Corr. 1B - H314; Eye Dam. 1 - H318
Environmental hazards Not Classified

2.2. Label elements**Pictogram****Signal Word**

Danger

SAFETY DATA SHEET

AKPEROX LPT-N

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Hazard statements	H242 H302 H314	Heating may cause a fire. Harmful if swallowed. Causes severe skin burns and eye damage.
Precautionary statements	P210 P220 P234 P280 P301+P310 P305+P351+P338 P411+P235 P501	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Nonsmoking. Keep away from amine and cobalt accelerators, acids, alkalis and heavy metalcompounds, combustible materials. Keep only in original container Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store at temperatures not exceeding 30°C. Keep cool. Dispose of contents/container in accordance with national regulations.

Supplemental label information RCH002 Restricted to professional users.

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Contains Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide		%25-40
REACH Reg. No: 01-2119514691-43-0007		
CAS Number	1338-23-4	EC Number
		700-954-4
Classification		
Org. Perox. D	H242	
Acute Tox. 4	H302	
Acute Tox. 4	H332	
Skin Corr. 1B	H314	
Eye Dam. 1	H318	

SAFETY DATA SHEET

AKPEROX LPT-N

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

BUTANONE		%1-5	
REACH Reg. No: 01-2119457290-43-0004			
CAS Number	78-93-3	EC Number	201-159-0
Classification			
Flam. Liq. 2	H225		
EUH066			
Eye Irrit. 2	H319		
STOT SE 3	H336		

DI-ISONONYL PHTHALATE		%60-80	
REACH Reg. No: 01-2119430798-28-0008			
CAS Number	28553-12-0	EC Number	249-079-5
Classification			
Not classified.			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Effects may be delayed. Keep affected person under observation. Chemical burns must be treated by a physician.
Inhalation	Remove affected person from source of contamination. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. DO NOT induce vomiting. Get medical attention immediately.
Skin contact	Remove affected person from source of contamination. Immediately remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

SAFETY DATA SHEET

AKPEROX LPT-N

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

4.2. Most important symptoms and effects, both acute and delayed

General information

Move out of dangerous areas. Show this Safety data sheet to the doctor in attendance. Do not leave the victim unattended. Symptoms of poisoning may appear several hours later. Call a physician immediately.

Inhalation

Nausea, vomiting. Dizziness.

Ingestion

May cause stomach pain or vomiting. Chemical burns.

Skin contact

May cause serious chemical burns to the skin.

Eye contact

May cause severe eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing Media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards

Vapours may form explosive mixtures with air. Forms explosive mixtures with air. May explode when heated or when exposed to flames or sparks. Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous decomposition products

Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Cool containers exposed to flames with water until well after the fire is out. Fight fire from safe distance or protected location. Move containers from fire area if it can be done without risk. Do not use water jet as an extinguisher, as this will spread the fire. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

SAFETY DATA SHEET

AKPEROX LPT-N

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Avoid or minimise the creation of any environmental contamination.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage. Do not touch or walk into spilled material. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate.

6.4. Reference to other sections

Reference to the other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid inhalation of vapours/spray and contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not handle broken packages without protective equipment.

Advice on general occupational hygiene Eye wash facilities and emergency shower must be available when handling this product. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving

SAFETY DATA SHEET

AKPEROX LPT-N

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

the work site. Good personal hygiene procedures should be implemented. Mechanical ventilation or local exhaust ventilation may be required. Container must be kept tightly closed when not in use.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Avoid contact with oxidising agents. Store away from the following materials: Acids. Alkalis. Keep away from flammable and combustible materials.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Components with workplace control parameters

Ingredients	CAS No.	Value	Control Parameters	Basis	Form of exposure
Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide	1338-23-4	C	0.2 ppm	ACGIH	
			0.2 ppm 1.5 mg/m ³	NIOSH REL	
			0.7 ppm 5 mg/m ³	OSHA P0	
			0.2 ppm 1.5 mg/m ³	CAL PEL	
Butanone	78-93-3	TWA	200 ppm	ACGIH	
		MPC-TWA	200 mg/m ³	RU OEL	Vapour and/or gas
		STEL	300 ppm	ACGIH	
		MPC-STEL	400 mg/m ³	RU OEL	Vapour and/or gas
		TWA	200 ppm 590 mg/m ³	NIOSH REL OSHA Z-1 OSHA P0 CAL PEL	
		ST	300 ppm 885 mg/m ³	NIOSH REL OSHA P0 CAL PEL	
Diisononyl phthalate	28553-12-0	TWA	5 mg/m ³	GB EH40	

SAFETY DATA SHEET

AKPEROX LPT-N

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Diisononyl phthalate	Workers	Dermal	Long-term systemic effects	366 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	51.72 mg/m ³
	Workers	Dermal	Long-term systemic effects	220 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	15.3 mg/m ³
	Workers	Oral	Long-term systemic effects	4.4 mg/kg bw/day
Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide	Consumers	Dermal	Long-term systemic effects	0.54 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0.41 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	0.27 mg/kg
	Workers	Dermal	Long-term systemic effects	1.08 mg/kg
	Workers	Inhalation	Long-term systemic effects	1.9 mg/m ³
Butanone	Workers	Inhalation	Long-term systemic effects	600 mg/m ³
	Workers	Dermal	Long-term systemic effects	1161 mg/kg
	Consumers	Inhalation	Long-term systemic effects	106 mg/m ³
	Consumers	Dermal	Long-term systemic effects	412 mg/kg
	Consumers	Ingestion	Long-term systemic effects	31 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide	Fresh water	0.0056 mg/l
	Marine water	0.00056 mg/l
	Intermittent use/release	0.056 mg/l
	Fresh water sediment	0.019 mg/kg
	Marine sediment	0.0019 mg/kg
	Sewage treatment plant	1.2 mg/l
	Soil	0.00231 mg/kg
Butanone	Fresh water	55.8 mg/l
	Marine water	55.8 mg/l
	Intermittent use/release	55.8 mg/l
	Fresh water sediment	284.74 mg/kg
	Marine sediment	284.74 mg/kg
	Sewage treatment plant	709 mg/l
	Soil	22.5 mg/kg

8.2. Exposure controls

Protective equipment

SAFETY DATA SHEET

AKPEROX LPT-N

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.



Appropriate engineering controls	Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.
Hand protection	Wear protective gloves made of the following material: Neoprene. Nitrile rubber. Rubber (natural, latex). The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Provide eyewash station and safety shower. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Check that the respirator fits tightly and the filter is changed regularly.
Environmental exposure controls	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Colorless
Odour	Characteristic.
Relative density	1,017±0,005 gr/cm ³ @20°C
Solubility(ies)	Partially soluble in water.
Flammability (solid, gas)	Not applicable
Viscosity	28 mPa.s (@20°C)



ORGANIC PEROXIDES, INITIATORS
PAINT DRIERS



SAFETY DATA SHEET

AKPEROX LPT-N

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

9.2. Other information

Active Oxygen Content 8,4 - 8,6%
SADT 60°C

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not available.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong alkalis. Strong acids. Strong reducing agents. Strong oxidising agents. Some metals.

10.6. Hazardous decomposition products

Hazardous decomposition Products Oxides of carbon. Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information
ATE oral (mg/kg) 300-2000 mg/kg

Serious eye damage/irritation: Causes burns.

Skin corrosion/irritation: Causes burns.

Respiratory or skin sensitisation:

SAFETY DATA SHEET

AKPEROX LPT-N

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Respiratory sensitisation	Based on available data the classification criteria are not met.
Germ cell mutagenicity:	
Genotoxicity - In Vitro - In Vivo	Based on available data the classification criteria are not met.
Carcinogenicity:	Based on available data the classification criteria are not met.
Reproductive Toxicity:	Based on available data the classification criteria are not met.
Reproductive Toxicity – Development	Based on available data the classification criteria are not met.
Specific target organ toxicity - single exposure:	
STOT - Single exposure	Based on available data the classification criteria are not met.
Specific target organ toxicity - repeated exposure:	
STOT - Repeated exposure	Based on available data the classification criteria are not met.
Aspiration Hazard	Based on available data the classification criteria are not met.
Inhalation	Harmful by inhalation. May cause damage to mucous membranes in nose, throat, lungs and bronchial system.
Ingestion	Irritating. May cause nausea, stomach pain and vomiting.
Skin contact	Prolonged and frequent contact may cause redness and irritation.
Eye contact	Causes burns.
Route of entry	Ingestion Inhalation Skin and/or eye contact
Target organs	Respiratory system, lungs
Medical considerations	Skin disorders and allergies.
<u>Toxicological information on ingredients.</u>	

Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide

Acute oral toxicity	LD50: 1017 mg/kg	Species: Rat
Acute inhalation toxicity	LC50 (Rat): 17 mg/l	Exposure time: 4h
Acute dermal toxicity	LD50: 4000 mg/kg	Species: Rat

Butanone

Acute oral toxicity	LD50: 2,737 mg/kg	Species: Rat
Acute dermal toxicity	LD50: 6,480 mg/kg	Species: Rabbit

SAFETY DATA SHEET

AKPEROX LPT-N

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Diisononyl phthalate

Acute oral toxicity	LD50: >1000 mg/kg	Species: Rat
Acute inhalation toxicity	LC50 (Rat): >4.4 mg/l	Exposure time: 4h
Acute dermal toxicity	LD50: >3160 mg/kg	Species: Rabbit

SECTION 12: Ecological Information

12.1. Toxicity

Ecological information on ingredients.

Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide

Toxicity to fish	LC ₅₀ , 96h: 44,2 mg/l
Toxicity to daphnia and other aquatic invertebrates	39 mg/l, 48h
Toxicity to algae	ErC ₅₀ , 72h: 5,6 mg/l
Toxicity to bacteria	EC ₁₀ , 0,5h: 5,6 mg/l

Butanone

Toxicity to fish	LC ₅₀ , 96h: 3.220 mg/l
------------------	------------------------------------

Diisononyl phthalate

Toxicity to fish	LC ₅₀ , 96h: >102 mg/l
Toxicity to daphnia and other aquatic invertebrates	EC ₅₀ , 48h: >74 mg/l
Toxicity to algae	EC ₅₀ , 72h: >88 mg/l

12.2. Persistence and degradability

Persistence and degradability The product is easily biodegradable.

12.3. Bio accumulative potential

Bio accumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product is partly miscible with water and may spread in the aquatic environment.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

SAFETY DATA SHEET

AKPEROX LPT-N

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Environmental Manager must be informed of all major spillages.

SECTION 14: Transport information

General information

For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

14.1. UN number

UN No. (ADR/RID)	3105
UN No. (IMDG)	3105
UN No. (ICAO)	3105
UN No. (ADN)	3105

14.2. UN proper shipping name

Proper Shipping name (ADR/RID)	ORGANIC PEROXIDE TYPE D, LIQUID (Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide)
Proper Shipping name (IMDG)	ORGANIC PEROXIDE TYPE D, LIQUID (Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide)
Proper Shipping name (ICAO)	ORGANIC PEROXIDE TYPE D, LIQUID (Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide)
Proper Shipping name (ADN)	ORGANIC PEROXIDE TYPE D, LIQUID (Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide)

14.3. Transport hazard class(es)

SAFETY DATA SHEET

AKPEROX LPT-N

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

ADR/RID class	5.2
ADR/RID label	5.2
IMDG class	5.2
ICAO class/division	5.2

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No

14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-J, S-R

Emergency Action Code 2W

Hazard Identification Number -
(ADR/RID)

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL Not Applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Health and Safety at Work etc. Act 1974 (as amended).
The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].
EH40/2005 Workplace exposure limits.

SAFETY DATA SHEET

AKPEROX LPT-N

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Key literature references and sources for data

This SDS is prepared based on the information received from the product owner.

Classification procedures according to Regulation (EC) 1272/2008

Skin Corr. 1B - H314; Acute Tox. 4 H302: Calculation Method. Org. Perox. D - H242: Expert Judgement.

Training advice

Read and follow manufacturer's recommendations. Only trained personnel should use this material.

Revision comments

Added REACH Number.

Issued By

Melih Babayiğit / CRAD Çevre Risk Analiz Denetim ve Eğitim Hizm. Ltd.Şti.
www.crad.com.tr Tel: +90216 335 4600

Issued Date

25.11.2009

Revised By

Simge ARIK
lab@akpakimya.com +90 282 361 80 99

Revision date

22.05.2019

Revision

3.0

Hazard statements in full

H225

Highly flammable liquid and vapour.

H242

Heating may cause a fire.

H302

Harmful if swallowed.

H314

Causes severe skin burns and eye damage.

H318

Causes serious eye damage.

H319

Causes serious eye irritation.

SAFETY DATA SHEET

AKPEROX LPT-N

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
Other abbreviations	
TWA	Time Weighted Average
STEL	Short term exposure limit
ACGIH	USA, ACGIH Thershold Limit Values (TLV)
PEL	Permissible exposure limits for chemical contaminants
NIOSH REL	USA NIOSH Recommended Exposure Limits
OSHA P0	USA OSHA – TABLE Z-1 Limits for ait contaminants – 1910.1000
OSHA Z-1	USA Occupational Exposure Limits (OSHA) – Table Z-1 Limits for air contaminants
ACGIH/TWA	8-hour, time-weighted average
ACGIH/STEL	Short-term exposure limit
ACGIH/C	Ceiling limit
CAL PEL/STEL	Short term exposure limit
CAL PEL/PEL	Permissible exposure limit
CAL PEL/C	Ceiling
NIOSH REL/TWA	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL/ST	STEL-15minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL/C	Celing value not be exceeded at any time
OSHA P0/TWA	8-hour time weighted average
OSHA P0/STEL	Short-term exposure limit
OSHA P0/C	Ceiling limit
OSHA Z-1/TWA	8-hour time weighted average

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.